

# Tarpapernails




Specification No.  
**ČSN 022812**



<b>Material:</b>	steel
<b>Strength:</b>	min. 490 MPa

Standard surface treatment
with no surface treatment
galv. zinc plated - white



d	2		2,5		2,8	
D	6,0		7,5		8,5	
l*	kg		kg		kg	
16	2 kg	2347	-	-	-	-
20	2 kg	1908	-	-	-	-
25	2 kg	1548	2 kg	925	-	-
32	-	-	2 kg	740	2 kg	571
36	-	-	2 kg	666	2 kg	512
40	-	-	-	-	2 kg	467
45	-	-	-	-	2 kg	418

## Comments:

- \* dimensions labelled with this mark can be changed
- No. of pieces in 1 kg
- weight of standard packaging unit

## Notes:

Standard thickness of surface treatment layer - 0,05 mm

# Lost head wire nails




Specification No.  
**ČSN 022820**



<b>Material:</b>	steel
<b>Strength:</b>	min. 637 MPa

<b>Standard surface treatment</b>
with no surface treatment
galv. zinc plated - white



d	2		2,5		2,8		3,15	
D	3		3,8		4,2		4,7	
l*								
32	-	-	-	-	-	-	-	-
36	-	-	-	-	-	-	-	-
40	2 kg	793	-	-	-	-	-	-
45	2 kg	714	-	-	-	-	-	-
50	2 kg	560	2 kg	460	-	-	-	-
56	2 kg	460	2 kg	416	2 kg	330	-	-
63	-	-	-	-	2 kg	297	2 kg	231
70	-	-	-	-	2 kg	270	2 kg	211
80	-	-	-	-	-	-	2 kg	186

## Comments:

- \* dimensions labelled with this mark can be changed
- No. of pieces in 1 kg
- weight of standard packaging unit

## Notes:

Standard thickness of surface treatment layer - 0,05 mm

# No head nails



Specification No.  
**ČSN 022865**



<b>Material:</b>	steel
<b>Strength:</b>	min. 637 MPa

Standard surface treatment
with no surface treatment
galv. zinc plated - white



d	2		2,5		2,8	
l*	kg		kg		kg	
16	2 kg		2 kg		2 kg	
20	2 kg		2 kg		2 kg	
25	2 kg		2 kg		2 kg	
32	2 kg		2 kg		2 kg	
35	2 kg		2 kg		2 kg	
36	2 kg		2 kg		2 kg	
40	2 kg		2 kg		2 kg	

## Comments:

- \* dimensions labelled with this mark can be changed
- No. of pieces in 1 kg
- weight of standard packaging unit

## Notes:

Standard thickness of surface treatment layer - 0,05 mm

# Knurled nails




Specification No.

**drawing No. 4-01-164**



<b>Material:</b>	steel
<b>Strength:</b>	min. 637 MPa

<b>Standard surface treatment</b>
with no surface treatment
galv. zinc plated - white



d	2		2,5		2,8		3,15		3,55		4	
D	5		6		7		8		9		10	
l*												
35	-	-	-	-	-	-	-	-	-	-	-	-
40	2 kg	890	-	-	-	-	-	-	-	-	-	-
45	2 kg	780	-	-	-	-	-	-	-	-	-	-
50	-	-	2 kg	507	2 kg	377	2 kg	320	-	-	-	-
56	-	-	2 kg	452	2 kg	359	2 kg	286	-	-	-	-
63	-	-	2 kg	403	2 kg	341	2 kg	255	-	-	-	-
70	-	-	-	-	2 kg	304	2 kg	229	2 kg	181	-	-
80	-	-	-	-	-	-	2 kg	202	2 kg	159	2 kg	123
90	-	-	-	-	-	-	2 kg	181	2 kg	141	2kg	110
100	-	-	-	-	-	-	-	-	-	-	2 kg	95
110	-	-	-	-	-	-	-	-	-	-	2 kg	90
120	-	-	-	-	-	-	-	-	-	-	2 kg	79

## Comments:

- \* dimensions labelled with this mark can be changed
- No. of pieces in 1 kg
- weight of standard packaging unit

## Notes:

Standard thickness of surface treatment layer - 0,05 mm

# Stainless nails



Specification No.

**drawing No. 4-01-140**



<b>Material:</b>	stainless steel
<b>Strength:</b>	min. 637 MPa

<b>Standard surface treatment</b>
with no surface treatment



d	2,5		3,15	
D	6		8	
l*	kg		kg	
40	1,42	100	-	-
50	1,97	100	3,12	100
56	2,21	100	3,49	100
63	2,48	100	3,92	100
70	-	-	4,35	100
80	-	-	4,95	100
90	-	-	5,52	100

## Comments:

\* dimensions labelled with this mark can be changed  
No. of pieces in 1 standard packaging unit  
 weight of 1 000 pieces



# Firmness nails with countersunk head



Specification No.

**drawing. No. 4-99-050**




<b>Material:</b>	steel
<b>Hardness:</b>	50 - 54 HRc

## Standard surface treatment

with no surface treatment

galv. zinc plated - white



<b>d</b>	<b>3,7</b>	
<b>D</b>	<b>6,5</b>	
<b>l*</b>		
30	500	2,46
35	500	2,87
40	500	3,27
45	300	3,71
50	300	4,14
60	300	5,70
70	300	6,20
90	300	8,40
120	300	13,20

## Comments:

\* dimensions labelled with this mark can be changed  
 No. of pieces in 1 standard packaging unit  
 weight of 1 000 pieces

# "DON" nails




Specification No.

**drawing No. 4-99-029**



<b>Material:</b>	steel
<b>Hardness:</b>	50 - 54 HRC

Standard surface treatment
with no surface treatment
galv. zinc plated - white



d	2,5		3,0		3,7	
D	4,8		5,8		7,4	
l*						
25	100	0,99	-	-	-	-
40	-	-	100	2,17	-	-
50	-	-	100	2,70	300	4,24
60	-	-	100	3,27	300	5,08
70	-	-	100	3,81	300	5,92

## Comments:

\* dimensions labelled with this mark can be changed  
 No. of pieces in 1 standard packaging unit  
 weight of 1 000 pieces

## Notes:

Standard thickness of surface treatment layer - 0,05 mm

# "Chapellet" nails



Specification No.

**drawing No. 4-99-048**




<b>Material:</b>	steel
<b>Strength:</b>	min. 637 Mpa

## Standard surface treatment

with no surface treatment

galv. zinc plated - white



<b>d</b>	2	
<b>D</b>	4	
<b>l*</b>		
16	1000	0,42
23	1000	0,60
30	1000	0,78

## Comments:

\* dimensions labelled with this mark can be changed  
No. of pieces in 1 standard packaging unit  
weight of 1 000 pieces





# Shoot-in nails - type P6



Specification No.

**MJ 001-2**




<b>Material:</b>	steel
<b>Hardness:</b>	50 - 54 HRc

## Standard surface treatment

with no surface treatment

galv. zinc plated - yellow



Type	with no washer		with S washer		with S+A washers	
d	3,7		3,7		3,7	
D	6		6		6	
I*						
20	500	2,08	500	3,28	500	3,45
22	500	2,17	500	3,37	500	3,54
27	500	2,45	500	3,65	500	3,82
32	500	2,86	500	4,06	500	4,23
37	500	3,29	500	4,49	300	4,66
42	300	3,70	300	4,90	300	5,07
47	300	4,15	300	5,35	300	5,52
52	300	4,55	300	5,75	300	5,92
57	300	4,89	300	6,09	300	6,26
62	300	5,50	300	6,70	300	6,87
67	300	6,06	300	7,26	300	7,33
70	300	6,45	300	7,65	-	-
80	300	6,99	-	-	-	-
87	300	7,49	-	-	-	-
92	300	7,87	-	-	-	-
120	300	10,35	-	-	-	-

## Notes:

Standard thickness of surface treatment layer - 0,05 mm

## Comments:

\* dimensions labelled with this mark can be changed  
 No. of pieces in 1 standard packaging unit  
 weight of 1 000 pieces

steel washer  
 plastic washer

# Shoot-in nails - type OP6



Specification No.


**MJ 001-2**



<b>Material:</b>	steel
<b>Hardness:</b>	50 - 54 HRc

## Standard surface treatment

with no surface treatment  
galv. zinc plated - yellow



Type	with no washer		with S washer		with S+A washers	
d	3,7		3,7		3,7	
D	6		6		6	
I*						
19	500	1,98	500	3,18	500	3,35
20	500	2,08	500	3,28	500	3,45
22	500	2,17	500	3,37	500	3,54
27	500	2,45	500	3,65	500	3,82
32	500	2,86	500	4,06	500	4,23

## Comments:

- \* dimensions labelled with this mark can be changed
- No. of pieces in 1 standard packaging unit
- weight of 1 000 pieces

- steel washer
- plastic washer

## Notes:

Standard thickness of surface treatment layer - 0,05 mm  
Shoot-in nails - type OP6 are knurled for shooting into steel.

# Shoot-in nails - type OPNH8




Specification No.

**MJ 001-2**



<b>Material:</b>	steel
<b>Hardness:</b>	50 - 54 HRc

Standard surface treatment
with no surface treatment
galv. zinc plated - yellow



Type	with no washer		with A washer	
d	3,7		3,7	
D	8		8	
I*				
19	500	2,38	500	2,45
22	500	2,49	500	2,54
27	500	2,89	500	2,79

## Comments:

- \* dimensions labelled with this mark can be changed
- No. of pieces in 1 standard packaging unit
- weight of 1 000 pieces
- plastic washer

## Notes:

Standard thickness of surface treatment layer - 0,05 mm

# Building nails with countersunk head




Specification No.  
**ČSN 022825**



<b>Material:</b>	steel
<b>Strength:</b>	min. 637 MPa

<b>Standard surface treatment</b>
galv. zinc plated - yellow
galv. zinc plated - white



d	2		2,5		2,8		3,15		3,55		4	
D	5		6		7		8		9		10	
l*												
35	-	-	-	-	-	-	-	-	-	-	-	-
40	2 kg	890	-	-	-	-	-	-	-	-	-	-
45	2 kg	780	-	-	-	-	-	-	-	-	-	-
50	-	-	2 kg	507	-	-	2 kg	320	-	-	-	-
56	-	-	2 kg	452	2 kg	359	2 kg	286	-	-	-	-
63	-	-	2 kg	403	2 kg	341	2 kg	255	-	-	-	-
70	-	-	-	-	2 kg	304	2 kg	229	2 kg	181	-	-
80	-	-	-	-	-	-	2 kg	202	2 kg	159	-	-
90	-	-	-	-	-	-	2 kg	181	2 kg	141	-	-
100	-	-	-	-	-	-	-	-	-	-	2 kg	95
110	-	-	-	-	-	-	-	-	-	-	2 kg	90
120	-	-	-	-	-	-	-	-	-	-	2 kg	79

## Comments:

- \* dimensions labelled with this mark can be changed  
 No. of pieces in 1 standard packaging unit  
 weight of 1 000 pieces

## Notes:

Standard thickness of surface treatment layer - 0,05 mm

# Shoot-in nails - type PNH8



Specification No.

**MJ 001-2**




<b>Material:</b>	steel
<b>Hardness:</b>	50 - 54 HRc

## Standard surface treatment

with no surface treatment

galv. zinc plated - white



Type	with no washer		with A washer	
d	3,7		3,7	
D	8		8	
I*				
22	500	2,49	500	2,56
27	500	2,89	500	2,96
32	500	3,29	500	3,36
37	500	3,69	500	3,76
42	300	4,09	300	4,16
47	300	4,49	300	4,56
52	300	4,89	300	4,96
57	300	5,29	300	5,36
62	300	5,72	300	5,79
67	300	6,09	300	6,16

## Comments:

- \* dimensions labelled with this mark can be changed
- No. of pieces in 1 standard packaging unit
- weight of 1 000 pieces
- plastic washer

## Notes:

Standard thickness of surface treatment layer - 0,05 mm